

Material Safety Data Sheet



STAIN BLASTER A

Section 1. Chemical product and company identification

Trade name : STAIN BLASTER A
Product use : Spot and Stain Remover
Supplier : Ecolab Inc. Institutional Division
370 N. Wabasha Street
St. Paul, MN 55102
1-800-352-5326
Code : 910704
Date of issue : 14-January-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352

Section 2. Composition, Information on Ingredients

| <u>Name</u> | <u>CAS number</u> | <u>% by weight</u> |
|--|-------------------|--------------------|
| benzenesulfonic acid, dodecyl-, compd. with 2,2',2''-nitrilotriethanol | 27323-41-7 | 10 |
| propan-2-ol | 67-63-0 | 4 |
| glycerin | 56-81-5 | 5 - 20 |
| tripropylene glycol monomethyl ether | 25498-49-1 | 1 - 5 |
| alcohols, c12-16, ethoxylated | 68551-12-2 | 1 - 5 |
| sodium metabisulphite | 7681-57-4 | 1 - 5 |
| a-amylase | 9000-90-2 | <1.0 |

Section 3. Hazards identification

Physical state : Liquid. (Liquid.)

Emergency overview : Caution!

MAY CAUSE ALLERGIC RESPIRATORY REACTION.
COMBUSTIBLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE.
MAY BE HARMFUL IF SWALLOWED.
MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION.
Repeated or prolonged contact with irritants may cause dermatitis.
Do not ingest. Do not get on skin or clothing. Do not breathe vapor or mist.
Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Moderately irritating to the eyes.

Skin : Slightly irritating to the skin.

Inhalation : Moderately irritating to the respiratory system. May cause sensitization by inhalation. Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.

Ingestion : Irritating to mouth, throat and stomach. Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.

See toxicological Information (section 11)

Section 4. First aid measures

- Eye contact** : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
- Skin contact** : Wash with soap and water. Get medical attention if irritation develops. Wash clothing before reuse.
- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion** : Rinse mouth; then drink one or two large glasses of water. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

- Flash point** : 43.3333 °C (Closed cup)
- Fire fighting media and instructions** : In case of fire, use water spray (fog), foam, dry chemicals, or CO₂.
- Dike area of fire to prevent product run-off.
- Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

- Handling** : Do not ingest. Avoid contact with eyes. Keep container closed. Use only with adequate ventilation. Do not breathe vapor or mist. Keep away from heat, sparks and flame. To avoid fire, minimize ignition sources. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Do not store above 50°C

Section 8. Exposure Controls, Personal Protection

Engineering controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

- Eyes** : Eye protection recommended.
- Hands** : For prolonged or repeated handling, use Impervious gloves.
- Skin** : No protective equipment is needed under normal use conditions.
- Respiratory** : Avoid breathing vapor or mist.

Name

glycerin

Exposure limits

ACGIH TLV (United States, 9/2004). Notes: Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM-TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract.

TWA: 10 mg/m³ 8 hour(s). Form: Mist

OSHA PEL (United States, 6/1993).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

propan-2-ol

ACGIH TLV (United States, 1/2004). Notes: ACGIH 2003 Adoption Refers to Appendix A -- Carcinogens.

STEL: 400 ppm 15 minute(s). Form: All forms

TWA: 200 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 6/1993).

TWA: 980 mg/m³ 8 hour(s). Form: All forms

TWA: 400 ppm 8 hour(s). Form: All forms

sodium metabisulphite

ACGIH TLV (United States, 5/2004). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens.

TWA: 5 mg/m³ 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

- Physical state** : Liquid. (Liquid.)
- Color** : Amber. (Light.)
- Odor** : Fragrance like.
- pH** : 7.68 (100%)
- Specific gravity** : 1.09 (Water = 1)
- Solubility** : Easily soluble in cold water, hot water.

Section 10. Stability and reactivity

- Stability** : The product is stable.

Section 11. Toxicological information

Potential acute health effects

- Eyes** : Moderately irritating to the eyes.
- Skin** : Slightly irritating to the skin.
- Inhalation** : Moderately irritating to the respiratory system. May cause sensitization by inhalation. Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.
- Ingestion** : Irritating to mouth, throat and stomach. Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.

Potential chronic health effects

- Chronic effects on humans** : Contains material which causes damage to the following organs: kidneys, mucous membranes, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea

Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂...), sulfur oxides (SO₂, SO₃...), phosphates. Some metallic oxides.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste classification : Unused product is D001 (Ignitable)

Consult your local or regional authorities.

Section 14. Transport information

| Regulatory information | UN number | Proper shipping name | Class | Packing group | Additional information |
|------------------------|----------------|----------------------|-------|---------------|------------------------|
| DOT Classification | Not regulated. | - | - | - | - |

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Combustible liquid
Irritating material
Sensitizing material
Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: None.

SARA 302/304 emergency planning and notification: None.

TSCA 8(b) inventory : All materials are listed or exempt.

California prop. 65 : No products were found.

Section 16. Other information

| | | | |
|---|----------------------------|---|---|
| Hazardous Material Information System (U.S.A.) | Health | * | 1 |
| | Fire hazard | | 2 |
| | Reactivity | | 0 |
| | Personal protection | | B |

Date of issue : 14-January-2005.

Responsible name : Regulatory Affairs

Date of previous issue : No Previous Validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.