

Material Safety Data Sheet



OASIS 255 SF

Section 1. Chemical product and company identification

Trade name : OASIS 255 SF
Product use : Glass Cleaner
Supplier : Ecolab Inc. Institutional Division
370 N. Wabasha Street
St. Paul, MN 55102
1-800-352-5326
Code : 909986
Date of issue : 23-December-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
2-butoxyethanol	111-76-2	9
ammonia	1336-21-6	1
2-propanol, 1-propoxy-	1569-01-3	5 - 20
2-aminoethanol	141-43-5	1 - 5

Section 3. Hazards identification

Physical state : Liquid. (Liquid.)
Emergency overview : WARNING!

CAUSES SEVERE EYE IRRITATION.
CAUSES RESPIRATORY TRACT AND SKIN IRRITATION.
Avoid contact with skin and clothing. Avoid breathing vapor or mist. Keep container closed.
Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Severely irritating to eyes.
Skin : Irritating to skin.
Inhalation : Irritating to respiratory system.
Ingestion : No known significant effects or critical hazards.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin contact : Wash with soap and water. Get medical attention if irritation occurs. Wash clothing before reuse.
Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

Section 5. Fire fighting measures

- Flash point** : 98.8889 °C (Closed cup)
- Fire hazards in the presence of various substances** : Because of the large amount of water contained in the product, it may be combustible only after partial or complete dehydration.
- Fire-fighting media and instructions** : Use an extinguishing agent suitable for the surrounding fire.
- Dike area of fire to prevent runoff.
No specific hazard.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

- Handling** : Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
Store between -10 and 50°C

Section 8. Exposure controls, personal protection

- Engineering controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

- Eyes** : Use safety eyewear designed to protect against splash of liquids.
- Hands** : Use chemical-resistant, impervious gloves.
- Skin** : No protective equipment is needed under normal use conditions.
- Respiratory** : Avoid breathing vapor or mist.

Name

2-butoxyethanol

Exposure limits

ACGIH TLV (United States, 1/2004).

TWA: 20 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997). Skin

TWA: 240 mg/m³ 8 hour(s). Form: All forms

TWA: 50 ppm 8 hour(s). Form: All forms

2-aminoethanol

ACGIH TLV (United States, 1/2004).

STEL: 15 mg/m³ 15 minute/minutes. Form: All forms

STEL: 6 ppm 15 minute/minutes. Form: All forms

TWA: 7.5 mg/m³ 8 hour(s). Form: All forms

TWA: 3 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 6 mg/m³ 8 hour(s). Form: All forms

TWA: 3 ppm 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

Physical state	: Liquid. (Liquid.)
Color	: Blue.
Odor	: Ammoniacal.
pH	: 11.2 (100%)
Boiling/condensation point	: 100 °C
Specific gravity	: 0.994 (Water = 1)
Dispersibility properties	: Easily dispersed in cold water, hot water.
Solubility	: Easily soluble in cold water, hot water.

Section 10. Stability and reactivity

Stability	: The product is stable.
Reactivity	: Reactive with acids. Slightly reactive to reactive with organic materials.

Section 11. Toxicological information

Potential acute health effects

Eyes	: Severely irritating to eyes.
Skin	: Irritating to skin.
Inhalation	: Irritating to respiratory system.
Ingestion	: No known significant effects or critical hazards.

Potential chronic health effects

Chronic effects on humans	: Contains material which causes damage to the following organs: blood, kidneys, lungs, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
---------------------------	--

Section 12. Ecological information

Products of degradation	: These products are carbon oxides (CO, CO ₂) and water, nitrogen oxides (NO, NO ₂ etc.).
-------------------------	--

Section 13. Disposal considerations

Waste disposal	: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
----------------	--

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	Not regulated.	-	-	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification	: Irritating material Target organ effects	
U.S. Federal regulations	: SARA 302/304/311/312 extremely hazardous substances: None. SARA 302/304 emergency planning and notification: None.	
TSCA 8(b) inventory	: All materials are listed or exempt.	
SARA 313	Product name	Concentration
Form R - Reporting requirements:	2-butoxyethanol	8.91 - 8.991
	ammonia	0.672 - 1.44
California Prop. 65	: No products were found.	

Section 16. Other information

Hazardous Material Information System (U.S.A.)	:	Health *	2
		Fire hazard	1
		Reactivity	0
		Personal protection	B
Date of issue	:	23-December-2005.	
Responsible name	:	Regulatory Affairs	
Date of previous issue	:	23-December-2005.	

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.